# FULL HEIGHT TURNSTILES

# LTF513

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Operation** | Adjustable manual passage to either direction. Optional: Motorized |
| **Chassis** | 10 mm tempered glass and 1.5 mm thick AISI 304 quality stainless steel. Optional: AISI 316 quality / with various color options, electrostatic powder coated |
| **Rotor and Arms** | 3 x 10 mm tempered glass and AISI 304 quality stainless steel rotor; Optional: AISI 316 / with various color options, electrostatic powder coated |
| **Functions** | Passage information, ability to set the passage time, memory mode, adjustable audio warning, remote controlled passage direction and enable feature.Integrated internal illumination |
| **Mechanism** | Tempered steel and zinc coating. |
| **Emergency Mode** | Fail-Safe (free entry/exit during power failure) Optional: Fail lock The arms allow free passage when the signal received from fire detection system. |

| | |
|---|---|
| **Operating Voltage** | 100-230 VAC, 47-60 Hz |
| **Power Consumption** | 7 W during passages, 12 W during stand-by |
| **Operating Temperature** | -20º / +70º Optional: with heater -50º |
| **Passage Speed** | ~20 persons/minute |
| **Passage Width** | 65 cm |
| **Weight** | ~430 kg |
| **Security Level** | High Security |
| **Indicators** | Standart in both directions |
| **Areas of Use** | Suitable for indoor and outdoor use |
| **Accessories** | Heater, Internal lightening, Stainless Steel Reader Bracket, Button Control Unit, Remote Control Unit, Coin Console, Stainless Steel Bottom Plate, RS232 / RS485 / LAN communication unit, adaptor |